TRI-CHEM

DOUBLE LUBE Chain & Cable Lubricant

DESCRIPTION (

Double Lube is a high temperature and pressure lubricant that penetrates chains, cables, and wire rope to deposit a wear-resistant coating. Double Lube can be used on conveyors, hoist chains, link and roller assemblies, railroad equipment, mining equipment, aircraft handling equipment, road and construction machinery, cutter bars, material handling equipment, chain saws, etc.

FOR USE ON

- Assemblies
- Chain Saws
- Cutter Bars
- Conveyors
- Aircraft Handling Equipment
- Hoist Chains
- Material Handling Equipment
- Link & Roller
- Road and Construction Machinery

FEATURES

- High temperature and pressure lubricant
- Penetrates to deposit a wear-resistant coating
- 14 oz. aerosol can

FIRST-AID

Eyes: Flush with copious amounts of water lifting lids and removing contact lenses to ensure complete irrigation—get medical attention.

Skin: Take off contaminated clothing and was before reuse. Gently blot or brush away excess product. Wash with plenty of lukewarm water for 15–20 minutes. Get medical attention if you feel unwell.

Inhalation: Remove to fresh air and keep comfortable for breathing. Get medical attention if you feel unwell.

Ingestion: Rinse mouth. Do NOT induce vomiting. Get medical attention immediately.

DIRECTIONS

Spray liberally on area to be treated. Allow to penetrate and apply final cover coat.

CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions and emergency procedures.

KEEP OUT OF REACH OF CHILDREN.



HMIS SYMBOL

