

## DOUBLE LUBE

### Chain & Cable Lubricant

---

#### DESCRIPTION

**Double Lube** is a high temperature and pressure lubricant that penetrates chains, cables, and wire rope to deposit a wear-resistant coating. Double Lube can be used on conveyors, hoist chains, link and roller assemblies, railroad equipment, mining equipment, aircraft handling equipment, road and construction machinery, cutter bars, material handling equipment, chain saws, etc.

---

#### FEATURES

- High temperature and pressure lubricant
- Penetrates to deposit a wear-resistant coating
- 14 oz. aerosol can

---

#### HOW TO USE

Spray liberally on area to be treated. Allow to penetrate and apply final cover coat.

---

#### SPECIFICATIONS

|                          |                     |
|--------------------------|---------------------|
| <b>Physical Form</b>     | Thick Liquid        |
| <b>Color</b>             | Black               |
| <b>Odor</b>              | Petroleum           |
| <b>Specific Gravity</b>  | 0.865               |
| <b>Flash Point (TOC)</b> | >222°F (Conc. Only) |

---

#### HMIS SYMBOL

|                     |   |
|---------------------|---|
| <b>Health</b>       | 1 |
| <b>Flammability</b> | 2 |
| <b>Reactivity</b>   | 0 |