

### DESCRIPTION

Oily Floor Primer is a concrete floor sealer/primer for use on floors contaminated with animal fat, cutting coolant, transmission fluid, etc.

### FIRST-AID

**Eyes:** Flush with copious amounts of water lifting lids and removing contact lenses to ensure complete irrigation—get medical attention.

**Skin:** Flush with water and then wash with soap and water, launder contaminated clothing before reuse—get medical attention if irritation persists.

**Inhalation:** Remove to fresh air and assist breathing as necessary—get medical attention.

**Ingestion:** Do NOT induce vomiting. Get medical attention.

### HMIS SYMBOL



Health	2
Fire	1
Reactivity	0
Personal Protection	

Part A



Health	2
Fire	2
Reactivity	0
Personal Protection	

Part B

### DIRECTIONS

- Clean application area as well as possible. The floor can be oil stained but standing water or oil must be removed.
- If oil is mixed with dirt, the oil/dirt combination must be scraped up prior to application of Oily Floor Primer. This material will adhere to the oily dirt, but oily dirt adheres poorly to floors. Applying over such contaminants will result in adhesion loss over time as dirt/oil mixture loosens adhesion. Oily Floor Primer is designed to work on oil stained surfaces; however better surface cleaning and preparation will result in better long-term adhesion. Wiping surface with a cleaning solvent-soaked rag will improve adhesion.
- Oily Floor Primer is mixed in a ratio of 2 Parts A to 1 Part B, either by weight or volume. Mix using a mechanical mixer or by hand with a mixing stick. Apply to surface using a paint brush, roller, or similar applicator.
- Oily Floor Primer is ready for foot traffic in approximately 12 hours and is ready for normal traffic in approximately 24 hours.
- Cure time will decrease if the temperature is above room temperature and increase when applied at temperatures below room temperature.
- Apply top coat 12-48 hours after application of primer to obtain best results.
- If a topcoat other than Oily Floor Color Coat is to be applied over the Oily Floor Primer, floor must be cleaned and degreased after Oily Floor Primer has completely cured and prior to application of topcoat.

### CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions and emergency procedures. KEEP OUT OF REACH OF CHILDREN.