

## THREE PATCH

### 100% Epoxy Concrete Patch

#### DESCRIPTION

Extreme Patch was designed to patch, fill, renew, and mend pits, cracks, holes, crevasses, and joints in concrete, steel, or wood. Extreme Patch is ideal for anchoring machinery, leveling and building up concrete, steel or wood ramps, walks, docks, parking garages, driveways, and floors. Extreme Patch is ideal for use in warehouses, refineries, plants, mills, machine shops, aircraft hangers, food processing facilities, railroads, subways, train stations, mines and quarries, laboratories.

#### FEATURES

- Pot Life: 30 minutes at 70°F
- Size: 6 Gallons
- Coverage: 60 sq. ft. at 1/8" thick or 30 sq. ft. at 1/4" thick

#### RECOMMENDATIONS

This product is designed for use on floor areas subjected to rough use as described herein, and corrosive or chemical spillage such as from alkalis, blood, fats, oils, salts, sugars, and other chemical compounds. Do not apply this product to floors that are in areas where temperatures may exceed 140°F on wood, or on asphaltic material. This compound is designed to provide results as described when used on structurally sound and properly prepared concrete, metal, or ceramic tile surfaces.

#### FIRST-AID

**Eyes:** Flush with copious amounts of water lifting lids and removing contact lenses to ensure complete irrigation—get medical attention.

**Skin:** Flush with water and then wash with soap and water, launder contaminated clothing before reuse—get medical attention if irritation persists.

**Inhalation:** Remove to fresh air—get medical attention.

**Ingestion:** Get medical attention.

#### HMIS SYMBOL



Health	2
Fire	1
Reactivity	0
Personal Protection	

**Part A**



Health	2
Fire	1
Reactivity	0
Personal Protection	

**Part B**



Health	0
Fire	0
Reactivity	0
Personal Protection	

**Part C**

#### CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions and emergency procedures.

KEEP OUT OF REACH OF CHILDREN.