

## TRI-COVER WHITE LATEX ROOF COATING

### DESCRIPTION

**Tri-Cover White Latex Roof Coating** is based on a synthetic latex system. It has two separate rubber-like polymers which increase flexibility, improve adhesion, maintain a brilliant white color, and improve the hiding power of the coating.

### FEATURES

- Brilliant white color reduces inside temperatures by reflecting the sun's rays
- Non-separating freeze-thaw stable product
- High solids content.
- Minimal shrinkage
- Maximum retention of applied coating to the surface after drying
- Coverage: On asphalt or metal surfaces: 1 to 1 ¼ gallons per 100 square feet

### HOW TO USE

- Repair cracks, breaks, open seams and other roof imperfections.
- Sweep off all dirt, dust and debris.
- Be sure there is no rust, mildew, oil, grease or other foreign coated material on the surface.
- The roof may be coated when damp, but not when there is standing water the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.
- Apply only when coating will not be subjected to heavy dew or rain before the coating has dried (approximately 5 hours).
- Remove any skins. Separation is usually slight but best procedure is to stir coating thoroughly to insure uniform application.
- Do not thin.
- It may be necessary to cool down a hot roof by spraying with water to prevent excessive fast dry of the coating. Coating may be applied over a damp surface.
- Pour coating onto a small area and spread with roller or large nylon brush.
- Apply uniformly, with a heavier coat around vents and seams.

### SPECIFICATIONS

<b>Physical Form</b>	Thick Liquid
<b>Color</b>	White
<b>Odor</b>	Ammonia
<b>Specific Gravity</b>	1.02
<b>Flash Point (TCC)</b>	None